



© 2021 Google

ACCESS TO DRIVEWAYS WILL BE PROVIDED UNLESS WORK IS BEING PERFORMED IN THAT AREA. Date: 05-12-2021

Posted Speed #	Formula	Minimum Desirable Taper Lengths #'		Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing #'	Suggested Longitudinal Buffer Spacing #'	
		10'	11'	12'	On a Taper			On a Tangent
30	L + WS/60	150'	165'	180'	30'	60'	120'	90'
35		205'	225'	245'	35'	70'	160'	120'
40		265'	295'	320'	40'	80'	240'	155'
45	L + WS	450'	495'	540'	45'	90'	320'	195'
50		500'	550'	600'	50'	100'	400'	240'
55		550'	605'	660'	55'	110'	500'	295'
60	L + WS	600'	660'	720'	60'	120'	600'	350'
65		650'	715'	780'	65'	130'	700'	410'
70		700'	770'	840'	70'	140'	800'	475'
75		750'	825'	900'	75'	150'	900'	540'

**LIFE & BARRICADE**  
 WWW.GUANG.NET  
 TCP DESIGNER:  
**ROBERT S. 214-748-5791**

**ROAD CLOSURE**  
 LAKESHORE BLVD  
 OAK POINT  
**RELIABLE PAVING**  
 Contact Name & Phone #: MARTY MURPHY 817-467-0779

DATE: 05-12-2021  
 PAGE: 1  
 SPEED LIMIT 40

This plan is for illustrative purposes only and has been designed to be a representation of the general operation of the traffic control devices for your project. Dallas Life & Barricade will not be held liable for any damages, losses, claims or liabilities whatsoever, whether direct or indirect, incidental, special, consequential, damages, that result from or in connection with the use which may be made of, or reliance upon, the information contained on this plan.